

ANTENNA SWITCH COMMON-USE UNIT

Publication number: JP6077707

Publication date: 1994-03-18

Inventor: ISHIZAKI TOSHIO; NAKAKUBO HIDEAKI; KOSUGI HIROAKI; AIZAWA KIMIO; IIZUKA SHOGO

Applicant: MATSUSHITA ELECTRIC IND CO LTD

Classification:

- International: H01P1/205; H01P1/15; H01P1/213; H03H7/46; H03K17/76; H04B1/48; H04B1/56; H01P1/10; H01P1/20; H03H7/00; H03K17/51; H04B1/44; H04B1/54; (IPC1-7): H01P1/213; H01P1/205; H03H7/46; H03K17/76; H04B1/48

- European:

Application number: JP19930168900 19930708

Priority number(s): JP19930168900 19930708; JP19920180849 19920708

Report a data error here

Abstract of JP6077707

PURPOSE: To obtain small-sized, simple structure with high performance and connect an antenna selectively to a transmitter or receiver by combining a switch device, a receiving filter, and an impedance adjusting element. **CONSTITUTION:** When a switch 200 is OFF, a PIN diode D1 turns OFF, the impedance viewed from an antenna terminal 10 to a transmission terminal 9 becomes almost infinitely large, and the signal at the terminal 10 is supplied to the receiver 102 through a BPF 8. When the switch 200 is ON, on the other hand, the D1 turns ON and its impedance becomes nearly zero. An air-core coil 6 is connected to a connection point P1 and the admittance viewed from the terminal 10 to the BPF 8 is almost zero at a transmission frequency. A reception terminal 11 is therefore electrically disconnected from the terminal 10 at the transmission frequency and the D1 turns ON, thereby connecting the terminal 10 to a transmitter 101.

